




Campus 58W DALI Datasheet

CCT 3000K/4000K/6000K 7250Lm - Up to 125Lm/W LED Batten

PXCAMPCTV4D



CE	UK CA	58W	IP20	LED	240V
----	----------	-----	------	-----	------

Dimensions	1490*200*81mm
Weight	2.35kg
Material	Steel body, PC diffuser
Colour/Finish	White
IK Rating	IK04
Voltage/Frequency	200-240V 50/60Hz
Luminous Flux	6960Lm/7250Lm/7134Lm
Luminous Efficacy	120-125Lm/W
Color Rendering Index	≥80
CCT Colour Temp	3000K/4000K/6000K Selectable
SDCM Colour Consistency	<5
UGR Unified Glare Rating	<19
LEDs	SMD 2835 320pcs
Light Control	DALI
Beam Angle	120°
Adjustable	No
Chip	Epistar
Maintained Luminous Flux	50,000h (L80B10), 65,000h (L70B50)
Warranty	5 Years

Features & Applications

The 4th generation 5ft DALI UGR<19 Campus surface luminaire is designed for academic buildings. Also available in emergency mode, this slim, contemporary style twin surface fitting provides up to 125Lm/W and an excellent quality of luminance for learning environments.

Ideal Application Areas Include:

Schools/Colleges, Office Developments, Retail Premises, Hotels and Leisure Facilities, Hospitals and Public Buildings.