


Pluto 35W CCT Datasheet

3375/3624/3338Lm Adjustable LED Downlight

PXPLU35WCCT



CE	UK CA	35W	IP20	LED	240V
----	----------	-----	------	-----	------

Dimensions	Ø180*147mm, Cut-Out Ø165-70mm
Weight	1.25Kg
Material	Aluminium
Colour/Finish	White
IK Rating	-
Voltage/Frequency	220-240V 50/60Hz
Luminous Flux	3375Lm/3624Lm/3338Lm
Luminous Efficacy	95-103Lm/W
Color Rendering Index	≥80
CCT Colour Temp	3000K/4000K/5700K
SDCM Colour Consistency	<6
UGR Unified Glare Rating	-
LEDs	COB 1pc
Light Control	Non-Dim
Beam Angle	60°
Adjustable	Rotates 90° (V), 350° (H)
Chip	Bridelux
Maintained Luminous Flux	30,000h (L80B10), 45,000h (L70B50)
Warranty	3 Years

Features & Applications

The Pluto adjustable CCT downlight comes with COB LEDs for excellent colour rendition.

The die-cast aluminium heat sink provides excellent thermal dissipation.

The fitting is tilttable 90° vertically and rotates 350° horizontally, making it an ideal option for retail stores and commercial premises.