


Trend CCT White 15W Datasheet

2700K/4000K/6000K 1222-1347-1385Lm LED Track Spotlight

PXTR15WCCT



CE	UK CA	15W	IP20	LED	240V
----	----------	-----	------	-----	------

Dimensions	ø74x170mm
Cut-Out	-
Weight	0.59kg
Material	Aluminium & PC
Colour/Finish	White
IK Rating	IK06
Voltage/Frequency	220-240V 50/60Hz
Luminous Flux	1222-1347-1385Lm
Luminous Efficacy	87.51-99.47Lm/W
Color Rendering Index	≥90
CCT Colour Temp	2700K/4000K/6000K Selectable
SDCM Colour Consistency	≤6
UGR Unified Glare Rating	≤19
LEDs	LY COB 1pc
Light Control	Triac Dim
Beam Angle	39°
Adjustable	350° (Horizontally), 90° (Vertically)
Chip	Bridgelux
IP Rating	IP20
Lifetime	35,000h (L80B10), 45,000h (L70B50)
Warranty	5 years

Features & Applications

The Trend 15W CCT range of LED track spots provide an excellent colour rendering index of ≥90 to increase the colour fidelity of the target illuminated object or space.

The 2700K/4000K/6000K selectable colour temperatures make this fitting highly adaptable to a wide variety of applications.

- 3 Circuit Fitting
- Colour Temperature Selectable
- Triac Dimmable
- Adjustable 350° Horizontally, 90° Vertically